

Laminex Finished DTV - Gloss - Panel

The Laminex Group

Chemwatch: 6614-22

Version No: 5.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 11/03/2014

Print Date: 29/10/2014

Initial Date: **Not Available**

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Laminex Finished DTV - Gloss - Panel
Chemical Name	Not Applicable
Synonyms	Laminex Finished Designed Timber Veneer - Gloss - Panel
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Used for the construction of furniture and cabinets for interior use.# Dust generated from shaping, cutting and sawing operations carried out on this product will contain cured binder/wood particles and may contain wood dust without binder. Wood dust is a hazardous substance according to the NOHSC criteria. and "may cause Sensitisation by inhalation and skin contact" (R42/43) and "may cause cancer by inhalation" (R49)
---------------------------------	--

Details of the manufacturer/importer

Registered company name	The Laminex Group
Address	90-94 Tram Road Doncaster 3108 VIC Australia
Telephone	+61 3 9848 4811
Fax	+61 3 9840 6513
Website	www.thelaminexgroup.com.au
Email	Not Available

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	0	
Toxicity	0	
Body Contact	0	
Reactivity	1	
Chronic	0	

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

Poisons Schedule	Not Applicable
GHS Classification	Not Applicable

Label elements

GHS label elements	Not Applicable
---------------------------	----------------

SIGNAL WORD	NOT APPLICABLE
--------------------	-----------------------

Hazard statement(s)

Not Applicable

Precautionary statement(s): Prevention

Not Applicable

Precautionary statement(s): Response

Not Applicable

Precautionary statement(s): Storage

Not Applicable

Precautionary statement(s): Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	10-30	timber veneer of nominated species
Not Available	NotSpec.	backing substrate containing
Not Available	1-10	paper
Not Available	NotSpec.	adhered to base panel containing
Not Available	30-60	wood particles
Not Available	NotSpec.	bonded together with
Not Available	NotSpec.	the panel will contain trace amounts of
108-95-2	NotSpec.	phenol
1330-20-7	NotSpec.	xylene
78-93-3	NotSpec.	methyl ethyl ketone
Not Available	NotSpec.	dust from sawing and forming operations will contain
Not avail.	NotSpec.	wood dust softwood
Not Available	NotSpec.	cured binder

*backing substrate containing adhered to base panel containing***SECTION 4 FIRST AID MEASURES****Description of first aid measures**

Eye Contact	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. ▶ Generally not applicable.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Continued...

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES**Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

Special hazards arising from the substrate or mixture**Fire Incompatibility**

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters**Fire Fighting**

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear breathing apparatus plus protective gloves.
- ▶ Prevent, by any means available, spillage from entering drains or water courses.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.

Fire/Explosion Hazard

Combustible. Will burn if ignited. Combustion products include: , carbon monoxide (CO), carbon dioxide (CO2), and minor amounts of, hydrogen cyanide, other pyrolysis products typical of burning organic material

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Minor Spills**

- ▶ Clean up all spills immediately.
- ▶ Secure load if safe to do so.
- ▶ Bundle/collect recoverable product.
- ▶ Collect remaining material in containers with covers for disposal.

Major Spills

- ▶ Clean up all spills immediately.
- ▶ Secure load if safe to do so.
- ▶ Bundle/collect recoverable product.
- ▶ Collect remaining material in containers with covers for disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling****Safe handling**

- ▶ Avoid generating and breathing dust
- ▶ Avoid contact with skin and eyes.
- ▶ Wear nominated personal protective equipment when handling.
- ▶ Use in a well-ventilated area.
- ▶ Use good occupational work practices.

Other information

- ▶ Store away from incompatible materials.

Conditions for safe storage, including any incompatibilities**Suitable container**

No restriction on the type of containers. Packing as recommended by manufacturer. Check all material is clearly labelled.

Storage incompatibility

- ▶ Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Continued...

Laminex Finished DTV - Gloss - Panel


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	phenol	Phenol	4 mg/m3 / 1 ppm	Not Available	Not Available	Sk
Australia Exposure Standards	xylene	Xylene (o-, m-, p-isomers)	350 mg/m3 / 80 ppm	655 mg/m3 / 150 ppm	Not Available	Not Available
Australia Exposure Standards	methyl ethyl ketone	Methyl ethyl ketone (MEK)	445 mg/m3 / 150 ppm	890 mg/m3 / 300 ppm	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
Laminex Finished DTV - Gloss - Panel	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
timber veneer of nominated species	Not Available	Not Available
backing substrate containing	Not Available	Not Available
paper	Not Available	Not Available
adhered to base panel containing	Not Available	Not Available
wood particles	Not Available	Not Available
bonded together with	Not Available	Not Available
the panel will contain trace amounts of	Not Available	Not Available
phenol	250 ppm	250 [Unch] ppm
xylene	1,000 ppm	900 ppm
methyl ethyl ketone	3,000 ppm	3,000 [Unch] ppm
dust from sawing and forming operations will contain	Not Available	Not Available
wood dust softwood	Not Available	Not Available
cured binder	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream. <p> When cutting wear approved dust respirator to avoid inhalation of wood dust created during the cutting process.</p>

Continued...

Thermal hazards	Not Available
------------------------	---------------

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Laminex Finished DTV - Gloss - Panel

Material	CPI
PE/EVAL/PE	A
TEFLON	A
BUTYL	C
BUTYL/NEOPRENE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
VITON	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P2	-	AX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AX-AUS / Class 1 P2	-
up to 100 x ES	-	AX-2 P2	AX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Multi-layer wood-based panel. Newly manufactured board or freshly cut surfaces may have a pine/wood odour		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available

Continued...

Laminex Finished DTV - Gloss - Panel

Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution(1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	<p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <ul style="list-style-type: none"> ▶ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. <p>[New boards or freshly cut surfaces may have a pine/wood/solvent odour which will dissipate with ventilation.]When cutting, wood dust will be created which is classified as a Hazardous Substance according to the criteria of NOHSC.[Atmosphere should be checked and if necessary suitable arrangements made to reduce the level of vapours in the breathing zone for persons working in the area.</p>
Ingestion	<p>The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).</p>
Skin Contact	<p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p>
Eye	<p>Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).</p>
Chronic	<p>This manufactured article is considered to have low hazard potential if handling and personal protection recommendations are followed.</p> <p>[The sealer for the the final topcoat contains toluene diisocyanate, which is s skin sensitiser, but this is expected to be fully reacted. When cutting new sheets there is a miniscule possibility that free isocyanate may be available - care should be taken and correct safety procedures followed to minimise exposure.</p>

Laminex Finished DTV - Gloss - Panel	TOXICITY	IRRITATION
	Not Available	Not Available
phenol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 850 mg/kg	Eye(rabbit): 100 mg rinse - mild
	Inhalation (rat) LC50: 316 mg/m3	Eye(rabbit): 5 mg - SEVERE
	Oral (rat) LD50: 317 mg/kg	Skin(rabbit): 500 mg open -SEVERE
	Not Available	Skin(rabbit): 500 mg/24hr - SEVERE
	Not Available	Not Available

Continued...

Laminex Finished DTV - Gloss - Panel

	TOXICITY	IRRITATION
xylene	Inhalation (rat) LC50: 5000 ppm/4h	Eye (human): 200 ppm irritant
	Intraperitoneal (Mouse) LD50: 1548 mg/kg	Eye (rabbit): 5 mg/24h SEVERE
	Intraperitoneal (Rat) LD50: 2459 mg/kg	Eye (rabbit): 87 mg mild
	Oral (Mouse) LD50: 2119 mg/kg	Skin (rabbit): 500 mg/24h moderate
	Oral (rat) LD50: 4300 mg/kg	
	Subcutaneous (Rat) LD50: 1700 mg/kg	
	Not Available	Not Available
methyl ethyl ketone	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 20000 mg/kg	- mild
	Dermal (rabbit) LD50: 6480 mg/kg	Eye (human): 350 ppm -irritant
	Inhalation (rat) LC50: 50100 mg/m ³ /8 hr	Eye (rabbit): 80 mg - irritant
	Inhalation (rat) LD50: 23500 mg/m ³ /8 hr	Skin (rabbit): 402 mg/24 hr - mild
	Oral (rat) LD50: 2737 mg/kg	Skin (rabbit): 13.78mg/24 hr open
	Not Available	Not Available
wood dust softwood	TOXICITY	IRRITATION
	Not Available	Not Available

Not available. Refer to individual constituents.

PHENOL	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.</p>
XYLENE	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.</p> <p>Reproductive effector in rats</p>
METHYL ETHYL KETONE	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.</p>
WOOD DUST SOFTWOOD	<p>No significant acute toxicological data identified in literature search.</p> <p>For wood dusts:</p> <p>Wood dusts may cause respiratory symptoms including sensitisation and diminished respiratory function and may also be carcinogenic.</p> <p>OSHA has determined that the health evidence for the toxicity of wood dust cannot be separately distinguished for soft wood and hard wood. A final OSHA ruling however establishes an 8-hour TWA PEL of 2.5 mg/m³ for Western red cedar wood dust, based on its widely recognized ability to cause immune-system-mediated allergic sensitization.</p> <p>WARNING: Inhalation of wood dust by workers in the furniture and cabinet making industry has been related to nasal cancer [I.L.O. Encyclopedia] Use control measures to limit all exposures.</p>

Continued...

Laminex Finished DTV - Gloss - Panel

Acute Toxicity	☹	Carcinogenicity	☹
Skin Irritation/Corrosion	☹	Reproductivity	☹
Serious Eye Damage/Irritation	☹	STOT - Single Exposure	☹
Respiratory or Skin sensitisation	☹	STOT - Repeated Exposure	☹
Mutagenicity	☹	Aspiration Hazard	☹

Legend: ✔ – Data required to make classification available
✘ – Data available but does not fill the criteria for classification
☹ – Data Not Available to make classification

CMR STATUS

SKIN	phenol	Australia Exposure Standards - Skin	Sk
------	--------	-------------------------------------	----

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
phenol	LOW (Half-life = 10 days)	LOW (Half-life = 0.95 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
methyl ethyl ketone	LOW (Half-life = 14 days)	LOW (Half-life = 26.75 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
phenol	LOW (BCF = 2.656)
methyl ethyl ketone	LOW (BCF = 3.162)

Mobility in soil

Ingredient	Mobility
phenol	LOW (KOC = 268)
methyl ethyl ketone	MEDIUM (KOC = 3.827)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Authority for disposal. ▶ Bury or incinerate residue at an approved site. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid	phenol	Y

Continued...

Laminex Finished DTV - Gloss - Panel

Substances Carried in Bulk		
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	xylene	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methyl ethyl ketone	Z

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

phenol(108-95-2) is found on the following regulatory lists	"Australia Exposure Standards", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
xylene(1330-20-7) is found on the following regulatory lists	"Australia Exposure Standards", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
methyl ethyl ketone(78-93-3) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
wood dust softwood(Not avail.) is found on the following regulatory lists	

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.